

Interiorluminaire for ceiling or suspended mounting. Suitable for use in schools.

Sheetmetal housing with RAL 9010 textured white paint. Endcaps of frosted acrylic glass. Doubleparabolic louvre with opal diffuser (SP).

Suspended fixture:

Opening on upper side of fixture for some light on the ceiling. Supplied with adjustable suspension wire and 2.5 m cable and plug.

Ceiling fitting:



With or without end inserts.

Dimmable version (TDC) equipped with Dali dimmable driver, push-button control and corridor function. Suspended version equipped with 5-wire connection cable.

Can be fitted with sensor and pull-switch.

Lifespan L80 Ta25 70000h (B50)
MacAdam 3 SDCM CRI: >80

IP 20 | CE



Accessory	Art no.	E-no.
Suspension wire for ceiling fixture	9 551 83	70 152 93
Rails for 600 T-section with slide screws	9 552 18	70 143 72
M6 clips for T-section	9 552 08	-

Suspended

Type	Lumen 830	Art no. 830	E-no.	Lumen 840	Art no. 840	E-no.	L	W	H	c/c	Power	Weight
ClassLED 5000	5090	1 592 14-U	70 108 26	5300	1 592 30-U	70 137 64	1260	152	50	1200	40	3
ClassLED 5000 TDC *	5090	1 592 15-U	70 108 28	5300	1 592 17-U	70 137 63	1260	152	50	1200	40	3
ClassLED 6000	6180	1 592 60-U	70 137 61	6440	1 592 62-U	70 137 62	1560	152	50	1310	50	3,5
ClassLED 6000 TDC *	6180	1 592 64-U	70 137 34	6440	1 592 66-U	70 137 35	1560	152	50	1310	50	3,5

Ceiling

Type	Lumen 830	Art no. 830	E-no.	Lumen 840	Art no. 840	E-no.	L	W	H	c/c	Power	Weight
ClassLED 2000	2090	1 592 10	70 118 28	2180	1 592 24	70 137 53	660	152	50	600	20	2
ClassLED 2000 TDC *	2090	1 592 12	70 118 29	2180	1 592 25	70 137 54	660	152	50	600	20	2
ClassLED 5000	4810	1 592 14	70 108 25	4950	1 592 13	70 137 51	1260	152	50	1200	40	3
ClassLED 5000 TDC *	4810	1 592 15	70 108 27	4950	1 592 21	70 137 52	1260	152	50	1200	40	3
ClassLED 6000	5840	1 592 60	70 137 59	6090	1 592 62	70 137 60	1560	152	50	1310	50	3,5
ClassLED 6000 TDC *	5840	1 592 64	70 137 81	6090	1 592 66	70 137 82	1560	152	50	1310	50	3,5

Ceiling with end connection

Type	Lumen 830	Art no. 830	E-no.	Lumen 840	Art no. 840	E-no.	L	W	H	c/c	Power	Weight
ClassLED 2000	2090	1 592 11	70 137 73	2180	1 592 27	70 137 78	660	152	50	600	20	2
ClassLED 2000 TDC *	2090	1 592 23	70 137 77	2180	1 592 28	70 137 79	660	152	50	600	20	2
ClassLED 5000	4750	1 592 16	70 137 74	4950	1 592 19	70 137 76	1260	152	50	1200	40	3
ClassLED 5000 TDC *	4750	1 592 18	70 137 75	4950	1 592 29	70 137 80	1260	152	50	1200	40	3
ClassLED 6000	5840	1 592 68	70 137 83	6090	1 592 70	70 137 84	1560	152	50	1310	50	3,5
ClassLED 6000 TDC *	5840	1 592 72	70 137 85	6090	1 592 74	70 137 86	1560	152	50	1310	50	3,5

* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.