

Luminaire for damp and dusty environments, multi-storey car parks, etc.

D-marked enclosed IP 66 fixture. Housing made of polycarbonate.

Frosted diffuser of polycarbonate. Stainless steel mounting clips. Detachable suspension brackets with adjustable c/c, distance +/- 25 mm.

Fitted flush to ceiling, on wallbracket, rails or wires.

Connection by 5-pole quickconnector in the ends, with internal throughwiring 5x2,5mm<sup>2</sup>. Making so it's not needed to open the housing when connecting wires.

IND is fitted with robust industrydriver with good resistance to voltagesurges.

Available in several versions with dimming.

Lifetime L80 Ta25 100000h (B50)  
MacAdam 3 SDCM CRI: >80

IP 66 D | IK 08 | CE





Quick connection in each end



Detachable suspension brackets

Accessory	Part no.	E-no.
Wire bracket (pair)	9 550 30	79 550 30
Shelterbracket	9 550 26	-
Adjustable bracket (pair)	9 550 18	79 550 19
45/90 bracket (pair)	9 550 10	79 550 10
45 bracket (pair)	9 550 11	-



With standard driver

Type	Lumen	Art. no.	E-no.	L	W	H	c/c	Power	Weight
ID 66 PC 8000 830	7930	4 527 71	72 156 99	1577	86	93	1000	53	3,2
ID 66 PC 8000 840	8260	4 527 73	72 157 14	1577	86	93	1000	53	3,2
ID 66 PC 6500 830	6620	4 527 75	72 157 15	1577	86	93	1000	43	3,2
ID 66 PC 6500 840	6900	4 527 77	72 157 16	1577	86	93	1000	43	3,2
ID 66 PC 5000 830	4860	4 527 79	72 157 17	1277	86	93	700	31	2,9
ID 66 PC 5000 840	5060	4 527 81	72 157 18	1277	86	93	700	31	2,9

With Industrydriver

Type	Lumen	Art. no.	E-no.	L	W	H	c/c	Power	Weight
ID 66 PC IND 8000 830	7930	4 527 83	72 157 19	1577	86	93	1000	53	3,2
ID 66 PC IND 8000 840	8260	4 527 85	72 157 28	1577	86	93	1000	53	3,2
ID 66 PC IND 6500 830	6620	4 527 87	72 157 29	1577	86	93	1000	43	3,2
ID 66 PC IND 6500 840	6900	4 527 89	72 157 39	1577	86	93	1000	43	3,2
ID 66 PC IND 5000 830	4860	4 527 91	72 157 40	1277	86	93	700	31	2,9
ID 66 PC IND 5000 840	5060	4 527 93	72 157 67	1277	86	93	700	31	2,9