

Luminaire for multifunctionceiling, ex shops.

Powdercoated housing RAL 9010
Doubleparabolic metallized anti-glare louvre with integrated opaldiffuser.


Fits in multifunctionceiling with c/c 1800 mm, profile with 160 mm and height 40mm. Other dimensions can be offered.

As standard without cabling. Can be fitted with a variety of cables and also quickconnectors (state when ordering).

Dimmable version (TDC) equipped with Dali dimmable driver, push-button control and corridor function.

Lifetime L80 Ta25 75000h (B50)
MacAdam 3 SDCM CRI: >80
IP 20 | CE

Accessory	Part. no.	E-no.
Cable 2,5m with earthed plug	9 551 66	-
Cable 2,5m with 3-phase adapter	9 551 68	-



Type	Lumen	Art. no.	E-no.	L	W	H	Power	Weight
Storeliner II 8000 830 18.1	8050	1 591 91	70 174 91	1640	101	50	74	3,6
Storeliner II 8000 840 18.1	8300	1 591 93	70 174 92	1640	101	50	74	3,6
Storeliner II 8000 830 18.1 TDC *	8050	1 591 95	70 174 93	1640	101	50	74	3,6
Storeliner II 8000 840 18.1 TDC *	8300	1 591 97	70 174 94	1640	101	50	74	3,6

* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.