

Asymmetric interiorluminaire.
Suitable for walls or whiteboardlighting.



Housing made from sheetmetal with RAL 9010 white textured paint. Frosted acrylic glass endcaps.

Mounting flush to ceiling, suspended or on wallbrackets. Accessories to be ordered separately.

Available in several versions depending on adjustment, control and connection options.

Lifespan: L80 Ta25 70000h (B50)
MacAdam 3 SDCM CRI: >80

IP 20 | CE



Accessories	Art no.	E no.
Suspension wire for ceiling fixture	9 551 83	70 152 93
Pair of wallbrackets	9 551 55	70 152 94
Kit for continuous mounting	9 551 56	70 152 95

Type	Lumen	Art no.	E no.	L	W	H	c/c	Power	Weight
ClassLED AS 3000 830	2880	1 592 47	70 137 55	1260	152	50	1200	36	3
ClassLED AS 3000 840	2990	1 592 48	70 137 56	1260	152	50	1200	36	3
ClassLED AS 3000 830 TDC *	2880	1 592 49	70 137 57	1260	152	50	1200	36	3
ClassLED AS 3000 840 TDC *	2990	1 592 50	70 137 58	1260	152	50	1200	36	3

* Equipped with amplitude-dimmable driver for DALI, push-button control and corridor function.