



Downlight for recessed fitting.

Rim of die casted aluminium, as standard white RAL 9016.

Other parts made from Aluzink, anodised aluminium cooling

Faceted high-gloss pure aluminium reflector.

40-degree beam angle.

Mounted to ceiling with spring clasps. Separate component unit as standard.

Comes as standard with Halogen-free 2.5 m cable with earthed plug
Dimmable version (TD) also equipped with separate 2-wires for control.

Lifespan L80 Ta25 50000h (B50)
MacAdam 3 SDCM CRI: >80

IP 21 | CE





Rails for soft ceilings



Plate for soft ceilings

Accessories	Art no.	E no.
Rails for soft ceilings	9 687 01	74 677 01
Plate for soft ceilings	9 665 45	75 011 49



Type	Lumen	Art no.	E no.	Power	Weight
Nemo 5 LED 1100 830	1330	2 815 01	74 679 72	10	1,3
Nemo 5 LED 1100 840	1390	2 815 03	74 679 73	10	1,3
Nemo 5 LED 2000 830	2030	2 815 13	74 679 74	15	1,3
Nemo 5 LED 2000 840	2120	2 815 15	74 679 75	15	1,3
Nemo 5 LED 1100 830 TD *	1330	2 815 21	74 679 76	10	1,3
Nemo 5 LED 1100 840 TD *	1390	2 815 23	74 642 85	10	1,3
Nemo 5 LED 2000 830 TD *	2030	2 815 25	74 679 53	15	1,3
Nemo 5 LED 2000 840 TD *	2120	2 815 26	74 642 86	15	1,3

* Equipped with Dali dimming driver or push-button.